

Refine Search

Search Results -

Terms	Documents
L13 same binary	4

Database:

US Pre-Grant Publication Full-Text Database
 US Patents Full-Text Database
 US OCR Full-Text Database
 EPO Abstracts Database
 JPO Abstracts Database
 Derwent World Patents Index
 IBM Technical Disclosure Bulletins

Search:

L14

Refine Search

Recall Text

Clear

Interrupt

Search History

DATE: Monday, May 09, 2005 [Printable Copy](#) [Create Case](#)

Set Name **Query**
 side by side

Hit Count **Set Name**
 result set

DB=USPT,USOC,EPAB,JPAB,DWPI,TDBD; PLUR=YES; OP=OR

<u>L14</u>	L13 same binary	4	<u>L14</u>
<u>L13</u>	L11 same compar\$	224	<u>L13</u>
<u>L12</u>	L11 and l6	5	<u>L12</u>
<u>L11</u>	L7 same l8	1240	<u>L11</u>
<u>L10</u>	L9 and l8	4	<u>L10</u>
<u>L9</u>	L6 same l7	576	<u>L9</u>
<u>L8</u>	known adj1 resistance	3354	<u>L8</u>
<u>L7</u>	voltage same resistance	340588	<u>L7</u>
<u>L6</u>	(programmable adj1 element) or antifuse	4130	<u>L6</u>

DB=USPT; PLUR=YES; OP=OR

<u>L5</u>	L4 same l3	1	<u>L5</u>
<u>L4</u>	L1 same l2	505	<u>L4</u>
<u>L3</u>	known adj1 resistance	2197	<u>L3</u>
<u>L2</u>	voltage same resistance	143518	<u>L2</u>

L1 (programmable adj1 element) or antifuse

2948 L1

END OF SEARCH HISTORY

[First Hit](#) [Fwd Refs](#)[Previous Doc](#)[Next Doc](#)[Go to Doc#](#)

Generate Collection

Print

L10: Entry 2 of 4

File: USPT

Jul 23, 2002

DOCUMENT-IDENTIFIER: US 6424161 B1

**** See image for Certificate of Correction ****

TITLE: Apparatus and method for testing fuses

Brief Summary Text (9):

Antifuses are typically fabricated with a structure similar to that of a capacitor, such that two conductive electrical terminals are separated by a dielectric layer. In the unprogrammed state, in which the antifuse is fabricated, there is a high resistance between the terminals, while in the programmed state, there is low resistance. To program an antifuse, a large programming voltage is applied across the antifuse terminals, breaking down the interposed dielectric and forming a conductive link between the antifuse terminals.

CLAIMS:

1. A method for testing a programmed fuse in an integrated circuit, the method comprising: selecting a control resistor fabricated to have a known resistance; measuring a testing time for the control resistor having the known resistance; measuring a testing time for the programmed fuse having an unknown resistance; and comparing the testing time for the programmed fuse against the testing time for the control resistor and determining the resistance of the programmed fuse therefrom. applying a voltage to the control resistor; and measuring a time period for the voltage to decay to a decayed voltage less than or equal to a reference voltage.
2. The method of claim 1, further comprising selecting a resistance value of the control resistor from a plurality of known resistances according to a design parameter.
4. The method of claim 1, wherein measuring the testing time for the control resistor further comprises: selecting the control resistor from a plurality of resistors having known resistances; initializing a reference voltage in a testing circuit; applying a pre-charge voltage across the control resistor; allowing the pre-charge voltage to decay; determining a first time at which the pre-charge voltage has decayed to a value less than the reference voltage in the testing circuit; adjusting the reference voltage in the testing circuit to obtain an updated reference voltage; applying the pre-charge voltage across the control resistor; allowing the pre-charge voltage to decay; determining a second time at which the pre-charge voltage has decayed to a value less than the reference voltage in the testing circuit; repeating adjusting through determining a second time if the second time is less than the first time; and selecting the first time as the testing time for the control resistor.
5. The method of claim 1, wherein measuring the testing time for the control resistor further comprises: selecting the control resistor from a plurality of resistors having known resistances; initializing a reference voltage in a testing circuit; applying a voltage across a control resistor; causing the voltage across the control resistor to charge; determining a first time at which the voltage across the control resistor has increased to a value greater than the reference voltage in the testing circuit; adjusting the reference voltage in the testing circuit to obtain an updated reference voltage; applying a voltage across the

control resistor; causing the voltage across the control resistor to charge; determining a second time at which the voltage across the control resistor has increased to a value greater than the reference voltage in the testing circuit; repeating adjusting through determining a second time if the second time is less than the first time; and selecting the first time as the testing time for the control resistor.

15. The method according to claim 14 wherein selecting the control resistor further includes selectively connecting at least two resistors having known resistances to produce a desired resistance value for the control resistor.

16. A method for testing a programmed fuse in an integrated circuit, comprising: selecting a control resistor having a known resistance; selecting a reference voltage; applying a test voltage across the control resistor; comparing the test voltage across the control resistor to the reference voltage; measuring a test time when the test voltage matches the reference voltage; selecting a programmed fuse having an unknown resistance; applying the test voltage across the programmed fuse; comparing the test voltage across the programmed fuse to the reference voltage; measuring a fuse time when the test voltage matches the reference voltage; comparing the test time to the fuse time to determine if the fuse was programmed correctly.

19. A method for testing a programmed fuse in an integrated circuit, the method comprising: selecting a control resistor on the integrated circuit which has a known resistance; measuring a testing time for the control resistor having the known resistance; measuring a testing time for the programmed fuse having an unknown resistance; and comparing the testing time for the programmed fuse against the testing time for the control resistor to determine if the programmed fuse was properly programmed.

20. A method for testing a programmed fuse in an integrated circuit, the method comprising: selecting a control resistor to have a selectable known resistance; selecting a resistance value for the control resistor; measuring a testing time for the control resistor; measuring a testing time for the programmed fuse having an unknown resistance; and comparing the testing time for the programmed fuse against the testing time for the control resistor to determine the resistance of the programmed fuse to determine if the programmed fuse was properly programmed.

22. A method for testing programmed fuses in an integrated circuit, comprising: selecting a control resistor onto the integrated circuit fabricated to have a known resistance; measuring a control testing time for the control resistor; selecting a first programmed fuse having an unknown resistance; measuring a first testing time for the first programmed fuse; comparing the testing time for the programmed fuse against the testing time for the control resistor to determine the resistance of the first programmed fuse; changing the control testing time to a changed control testing time; selecting a second programmed fuse; measuring a second testing time for the second programmed fuse; and comparing the second testing time for the second programmed fuse to the changed control testing time to determine the resistance of the second programmed fuse.

23. A method for testing the state of a programmed anti-fuse in an integrated circuit, the method comprising: fabricating a control resistor on the integrated circuit to have a plurality of selectable resistance values; selecting a known resistance value for the control resistor from the plurality of selectable resistance values; measuring a decay time for the control resistor to produce a known decay time corresponding to the known resistance value; measuring a decay time for the programmed anti-fuse having an unknown resistance value; and comparing the decay time for the programmed anti-fuse to the known decay time to determine the resistance value of the programmed anti-fuse.

24. A method for testing a programmed anti-fuse in an integrated circuit, the method comprising: fabricating a control resistor on the integrated circuit to have a plurality of selectable resistance values; selecting a known resistance value for the control resistor from the plurality of selectable resistance values; applying a pre-charge voltage across the control resistor; comparing a decay voltage for the control resistor to a reference voltage to produce a known decay time corresponding to the known resistance value; applying the pre-charge voltage across the programmed anti-fuse; comparing a decay voltage for the programmed anti-fuse to the reference voltage to determine an anti-fuse decay time for the programmed anti-fuse; and comparing the known decay time to the anti-fuse decay time to determine if the anti-fuse was properly programmed.

25. A method for testing a programmed anti-fuse in an integrated circuit, the method comprising: fabricating a control resistor on the integrated circuit to have a plurality of selectable resistance values; selecting a known resistance value for the control resistor from the plurality of selectable resistance values; applying a pre-charge voltage across the control resistor; comparing a decay voltage for the control resistor to a reference voltage; measuring the time it takes for the decay voltage to match the reference voltage and producing therefrom a decay time for the control resistor; adjusting the reference voltage to produce an adjusted reference voltage; applying the pre-charge voltage across the control resistor; comparing the decay voltage for the control resistor to the adjusted reference voltage; measuring the time it takes for the decay voltage to match the adjusted reference voltage and producing therefrom a new decay time for the control resistor; applying the pre-charge voltage across a programmed anti-fuse; comparing a decay voltage for the programmed anti-fuse to the adjusted reference voltage; measuring the time it takes for the decay voltage to match the adjusted reference voltage to determine if the programmed anti-fuse was properly programmed.

[Previous Doc](#)

[Next Doc](#)

[Go to Doc#](#)



US006424161B2

(12) **United States Patent**
Damon et al.

(10) **Patent No.:** **US 6,424,161 B2**
(45) Date of Patent: ***Jul. 23, 2002**

(54) **APPARATUS AND METHOD FOR TESTING FUSES**

(75) **Inventors:** **Tim Damon, Meridian; Phillip E. Byrd, Boise, both of ID (US)**

(73) **Assignee:** **Micron Technology, Inc., Boise, ID (US)**

(*) **Notice:** This patent issued on a continued prosecution application filed under 37 CFR 1.53(d), and is subject to the twenty year patent term provisions of 35 U.S.C. 154(a)(2).

Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) **Appl. No.:** **09/146,688**

(22) **Filed:** **Sep. 3, 1998**

(51) **Int. Cl.**⁷ **G01R 31/02; G01R 27/26; H01H 31/02**

(52) **U.S. Cl.** **324/550; 324/537; 324/677**

(58) **Field of Search** **324/550, 537, 324/711, 677**

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,206,583 A * 4/1993 Dawson et al. 324/721
 5,313,165 A * 5/1994 Brokaw 324/158.1
 5,768,290 A 6/1998 Akamatsu 371/22.4
 5,841,789 A * 11/1998 McClure 327/276

5,896,039 A * 4/1999 Brannigan et al. 324/763
 5,952,833 A * 9/1999 Morgan 324/537
 6,018,481 A 1/2000 Shiratake 365/190
 6,256,239 B1 7/2001 Akita et al. 365/200
 6,268,763 B1 * 7/2001 Fujikawa 327/541

* cited by examiner

Primary Examiner—Michael J. Sherry

Assistant Examiner—Jermele Hollington

(74) *Attorney, Agent, or Firm*—Schwegman, Lundberg, Woessner & Kluth, P.A.

(57) **ABSTRACT**

A voltage is applied across a control resistor, and the voltage is caused to decay. The decay is monitored by a testing circuit such as a comparator. When the voltage across the control resistor has decayed to a value less than or equal to a reference voltage in the comparator, a switch time period is established. Fuses in a memory device are tested against the established switch time period. The fuses are tested in a similar fashion: a voltage is applied across the fuse being tested, and the voltage is caused to decay. The comparator monitors the decay of the voltage across the fuse. If the resistance value of a fuse being tested is within specification, the comparator changes its state at a time equal to or less than the switch time period established for the control resistor. Testing time for fuses can further be minimized by having an external access to the reference in the comparator. In establishing the switch time period by applying a voltage across the control resistor, the voltage of the reference in the comparator is adjusted to establish quicker switch time periods against which fuses are tested. In this manner, testing time is minimized.

25 Claims, 7 Drawing Sheets

